

# TYPE B NON-METALLIC FITTINGS

## UL LISTED AND CSA APPROVED

### NON-METALLIC FITTINGS

#### FITTINGS FOR NMUA/NMEF TYPE B ONLY



#### DESCRIPTION

- All type nylon 66 construction with O-ring and steel lock nut included
- Reusable and durable fittings are flame retardant and resist salt water, weak acids, gasoline, alcohol, oil grease and common solvents

#### INSTALLATION

- Fittings used with standard non-metallic **Type B** conduit for easy installation
- Approved for both exposed and concealed locations
- Easy to install, by pushing the non-metallic conduit onto the smooth ferrule and tightening the sealing nut
- Manufactured in a full range of trade sizes from 3/8" through 2"
- Complies with NEC Article 356 and UL Standard 514B File No. E-322120
- Straight fittings approved for direct burial and in concrete trade sizes 3/8" through 2"

#### SPECIFICATIONS

- Color: Gray
- Temp. range: Dry: (0°F to +194°F (-18°C to +90°C))
- UV (sunlight) resistant
- UL Approved File No. E322120
- CSA Approved #620817
- Complies with NEMA standard FB-1

#### COMPLIANT WITH NEC ARTICLES


- 250.102 Equipment Bonding Jumpers
- 250.134 (B) Equipment Grounding
- 356 Liquid tight Flexible Nonmetallic Conduit (LFNC-B)
- Suitable for hazardous locations per NEC Articles
  - 501.10 (B) (2) Class I Div. 2
  - 502.10 (A) (2) and (B) (2) Class II Div. 1 & 2
  - 503.10 (A) (3) and (B) Class III Div. 1 & 2
- 620.21 Elevator Wiring Methods
- 645.5 (E) (2) Under Raised Floors

See: [www.ul.com](http://www.ul.com) [www.csa-international.org](http://www.csa-international.org)  
[www.nfpa.org](http://www.nfpa.org) [www.naed.org](http://www.naed.org)  
[www.nema.org](http://www.nema.org) [www.anacondasealtite.com](http://www.anacondasealtite.com)

### 3 PIECE: STRAIGHT




Trade Size	Item ID (Gray)	Item ID (Black)*	Dimensions (inches)			KO Size NPT	Weight (lbs/Pkg)	Std. Pkg.
			A	B	C			
3/8"	500001	-	1.545	0.535	1.400	1/2"	1.25	25
1/2"	500002	510002	1.545	0.535	1.400	1/2"	1.25	25
3/4"	500003	510003	1.600	0.550	1.700	3/4"	0.7	10
1"	500004	-	1.975	0.670	2.000	1"	0.7	5
1-1/4"	500005	-	2.293	0.645	2.400	1-1/4"	1	5
1-1/2"	500006	-	2.175	0.660	2.670	1-1/2"	0.6	5
2"	500007	-	2.400	0.670	3.280	2"	0.8	2



### 90 DEGREE

Trade Size	Item ID (Gray)	Item ID (Black)*	Dimensions (inches)			KO Size NPT	Weight (lbs/Pkg)	Std. Pkg.
			A	B	C			
3/8"	500008	-	2.242	0.562	3.120	1/2"	0.5	10
1/2"	500009	510009	2.242	0.562	3.120	1/2"	0.5	10
3/4"	500010	510010	2.550	0.545	3.600	3/4"	1	10
1"	500011	-	3.150	0.630	4.125	1"	0.8	5
1-1/4"	500012	-	3.420	0.645	5.200	1-1/4"	1.4	2
1-1/2"	500013	-	4.510	0.660	5.200	1-1/2"	0.8	2
2"	500014	-	4.850	0.670	5.800	2"	1	1



\* Black fittings will not be available after current inventory is sold.

IP 66/67 with approved conduit